


Plate

3003-H14

Mill Finish — Non-Heat Treatable
AMS QQ-A-250/2, ASTM B209,
AMS 4008




Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per PLT.
.250	48	120	3.564	142.560
	48	144	3.564	171.072
.375	48	144	5.346	256.608
.500	48	144	7.128	342.144
.750	48	144	10.690	513.120

Plate

5052-H32

Mill Finish — Non-Heat Treatable
AMS QQ-A-250/8, ASTM B209,
AMS 4016




Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per PLT.
.250	36	96	3.492	83.808
	36	120	3.492	104.760
	36	144	3.492	125.712
	48	96	3.492	111.744
	48	120	3.492	139.680
	48	144	3.492	167.616
	60	96	3.492	139.680
	60	120	3.492	174.600
	60	144	3.492	209.520
.375	48	144	5.238	251.424
.500	48	144	6.984	335.232
.750	48	144	10.480	503.040
1.000	48	144	13.970	670.560

Plate

2024-T351

Mill Finish — Heat Treatable
AMS QQ-A-250/4, ASTM B209,
AMS 4037




Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per PLT.
.250	48.5	144.5	3.600	175.212
.313	48.5	144.5	4.510	219.501
.375	48.5	144.5	5.400	262.818
.500	48.5	144.5	7.200	350.424
.625	48.5	144.5	9.000	438.030
.750	48.5	144.5	10.800	525.636
.875	48.5	144.5	12.600	613.242
1.000	48.5	144.5	14.400	700.848
1.250	48.5	144.5	18.00	876.060
1.500	48.5	144.5	21.600	1051.272
1.750	48.5	144.5	25.200	1226.484
2.000	48.5	144.5	28.800	1401.696
2.500	48.5	144.5	36.000	1752.120
3.000	48.5	144.5	43.200	2102.544
3.500	48.5	144.5	50.44	2454.914
4.000	48.5	144.5	57.600	2803.392
4.500	48.5	144.5	64.800	3153.816
5.000	48.5	144.5	72.000	3504.240
6.000	48.5	144.5	86.400	4205.088

Plate

6061-T651

Mill Finish — Heat Treatable
AMS QQ-A-250/11, ASTM B209,
AMS 4027




Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per PLT.
.250	48.5	144.5	3.528	171.707
	60.5	144.5	3.528	214.848
.313	48.5	144.5	4.417	214.975
	60.5	144.5	4.417	268.156
.375	48.5	144.5	5.292	257.561
	60.5	144.5	5.292	321.277
.500	48.5	144.5	7.056	343.415
	60.5	144.5	7.056	428.369
.625	48.5	144.5	8.820	429.269
	60.5	144.5	8.820	535.462
.750	48.5	144.5	10.584	515.123
	60.5	144.5	10.584	642.554
.875	48.5	144.5	12.348	600.977
	60.5	144.5	12.348	749.647
1.000	48.5	144.5	14.112	686.831
	60.5	144.5	14.112	856.739
1.250	48.5	144.5	17.640	858.538
	60.5	144.5	17.640	1070.924
1.500	48.5	144.5	21.168	1030.246
	60.5	144.5	21.168	1285.109
1.750	48.5	144.5	24.696	1201.954
	60.5	144.5	24.696	1499.294
2.000	48.5	144.5	28.224	1373.662
	60.5	144.5	28.224	1713.479
2.250	48.5	144.5	31.752	1545.369
	60.5	144.5	31.752	1927.663

Plate

6061-T651

Mill Finish — Heat Treatable
AMS QQ-A-250/11, ASTM B209,
AMS 4027



Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per PLT.
2.500	48.5	144.5	35.280	1717.077
	60.5	144.5	35.280	2141.848
2.750	48.5	144.5	38.808	1888.785
	60.5	144.5	38.808	2356.033
3.000	48.5	144.5	42.336	2060.049
	60.5	144.5	42.336	2570.218
3.500	48.5	144.5	49.392	2403.908
4.000	48.5	144.5	56.448	2747.324
4.500	48.5	144.5	63.504	3090.739
5.000	48.5	144.5	70.560	3434.155
5.500	48.5	144.5	77.616	3777.570
6.000	48.5	144.5	84.672	4120.986
7.000	48.5	144.5	98.784	4807.817
8.000	48.5	144.5	112.896	5494.648
9.000	48.5	144.5	127.008	6181.479
10.000	48.5	144.5	141.120	6868.310
12.000	48.5	144.5	169.344	8241.972


Plate

7075-T651, T7351

Mill Finish — Heat Treatable

AMS QQ-A-250/12, ASTM B209,


AMS 4045, AMS 4078



Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per PLT.
.250	48.5	144.5	3.636	176.964
.313	48.5	144.5	4.552	221.545
.375	48.5	144.5	5.454	265.446
.500	48.5	144.5	7.272	353.928
.625	48.5	144.5	9.090	442.410
.750	48.5	144.5	10.908	530.892
.875	48.5	144.5	12.726	619.374
1.000	48.5	144.5	14.544	707.856
1.250	48.5	144.5	18.180	884.820
1.500	48.5	144.5	21.816	1061.784
1.750	48.5	144.5	25.452	1238.748
2.000	48.5	144.5	29.088	1415.712
2.250	48.5	144.5	32.724	1592.677
2.500	48.5	144.5	36.360	1769.641
2.750	48.5	144.5	39.996	1946.605
3.000	48.5	144.5	43.632	2123.569
3.500	48.5	144.5	50.904	2477.497
4.000	48.5	144.5	58.176	2831.425
4.500	48.5	144.5	65.448	3185.354
5.000	48.5	144.5	72.720	3539.282
6.000	48.5	144.5	87.264	4247.138
7.000	48.5	144.5	101.808	4954.995
8.000	48.5	144.5	116.352	5662.851

Plate


MIC 6 Cast Tooling



Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per PLT.
.250	48.5	144.5	3.636	176.964
	60.5	144.5	3.636	220.741
.375	48.5	144.5	5.454	265.446
	60.5	144.5	5.454	331.112
.500	48.5	144.5	7.272	353.928
	60.5	144.5	7.272	441.483
.625	48.5	144.5	9.090	442.241
	60.5	144.5	9.090	551.853
.750	48.5	144.5	10.908	529.038
	60.5	144.5	10.908	662.224
1.000	48.5	144.5	14.544	707.856
	60.5	144.5	14.544	882.966
1.250	48.5	144.5	18.180	884.820
	60.5	144.5	18.180	1103.707
1.500	48.5	144.5	21.816	1061.784
	60.5	144.5	21.816	1324.449
1.750	48.5	144.5	25.452	1238.748
	60.5	144.5	25.452	1545.190
2.000	48.5	144.5	29.088	1415.712
2.500	48.5	144.5	36.360	1769.641
3.000	48.5	144.5	43.632	2123.569
4.000	48.5	144.5	58.176	2831.425

Plate

6061
Tread



Decimal Thickness	Width	Length	Approx WT. Per SQ. FT.	Approx WT. Per SQ. FT.
.125	48	192	1.900	121.60
	60	144	1.900	114.00
	60	192	1.900	152.00
.250	48	192	3.700	236.80
	60	192	3.700	296.00
.375	48	192	5.490	351.36
	60	192	5.490	439.20
.500	48	192	7.270	465.28
	60	192	7.270	581.60